

# Safety Data Sheet

# TM3-SDS

Rev. Date: Aug 17, 2021

Revision: 4

Page 1 of 7

P.O. Box 3286 - Logan, Utah 84323, U.S.A. - Tel. (800) 729-8350 - Tel. (435) 755-9848 - Fax (435) 755-0015 - www.scytek.com

# Section 1. Identification of the Substance/Mixture and the Company

1.1 Product Identifier	Product Name: TN Product Number:	MB Precipitating Reagent (Standard Sensitivity) TM3
1.2 Intended use	DA: Laboratoriere DE: Laboratorium EL: Αντιδραστήρι ES: Reactivo de la FR: Réactif de lab IT: Laboratorio d NL: Laboratorium PT: Reagente de	agent. For professional use only. agens. Kun til professionelt brug. reagens. Alleen voor professioneel gebruik. ο εργαστηρίου. Για επαγγελματική χρήση μόνο. aboratorio. Sólo para uso profesional. poratoire. Pour un usage professionnel uniquement. i reagente. Solo per uso professionale. reagens. Alleen voor professioneel gebruik. laboratório. Para uso profissional. agens. Endast för yrkesmässig användning.
1.3 Details of the	Manufacturer	ScyTek Laboratories, Inc.
supplier of the safety data sheet	Address	205 South 600 West Logan, Utah 84321 U.S.A.
	Phone Number	800-729-8350
	Fax Number	435-755-0015
	e-mail	scytek@scytek.com
	Website	scytek.com
1.4 Emergency Telephone	Chemtrec (USA): 1	-800-424-9300

#### Section 2. Hazards Identification

2.1 GHS	Flammable liquids (Category	3) – H226
Classification	Acute toxicity, Oral (Category	v 4) – H302
	Acute toxicity, Inhalation (Cat	tegory 4) – H332
	Acute toxicity, Dermal (Categ	ory 4) – H312
	Specific target organ toxicity	- single exposure (Category 2) – H371
2.2 Label	Pictogram(s):	$\wedge$
Elements		
	Signal Word:	Danger
	Hazard Statement(s):	H226 – Flammable liquid and vapor
		H302 + H312 + H332 – Harmful if swallowed, in contact with skin or if
		inhaled
		H371 – May cause damage to organs



Rev. Date: Aug 17, 2021

**Revision: 4** 

Page 2 of 7

P.O. Box 3286 - Logan, Utah 84323, U.S.A. - Tel. (800) 729-8350 - Tel. (435) 755-9848 - Fax (435) 755-0015 - www.scytek.com

	Precautionary statement(s):	P202 – Do not hand and understood	dle u	until all safety precautions [on SDS] have been read
	Precautionary statements not listed on label:	P305 + P351+P315 minutes. Get immed P301 + P310 - IF SV doctor/physician. P210 – Keep away smoking.	5 – II diate WAI fron	SKIN: Gently wash with plenty of soap and water F IN EYES: Rinse cautiously with water for several e medical advice/attention LLOWED: Immediately call a POISON CENTER or n heat/sparks/open flames/hot surfaces. – No dust/ fume/ gas/ mist/ vapours/ spray.
NFPA Scale: 0-4 (Estimated for Mixtures and Kits)	2 0			
HMIS (U.S.A.)	HEALTH	2	2	
Scale: 0-4	FLAMMABILITY	1		
(Estimated for Mixtures and Kits)	PHYSICAL HAZARD	0	)	
a. ee and rate)	PERSONAL PROTECTION	ı G	}	
2.3 Other Hazards	PBT: This mixture does not cont vPvB: This mixture does not cor	•		

### Section 3. Composition and Information on Ingredients

#### 3.2 Chemical Description: Mixture

\*May contain additional non-hazardous proprietary ingredients.

\*May contain additional active ingredients at concentrations <0.1%w/v.

Hazardous Ingredients:	CAS#	EC#	GHS Symbols	%
Methanol	67-56-1	200-659-6	Danger. 3 H225 Highly flammable liquid and vapour.  Danger. 3. H301 Toxic if swallowed. 3 H311 Toxic in contact with skin. 3 H331 Toxic if inhaled.  Danger. 1 H370 Causes damage to organs.	≤ 30
Dimethylsulfoxide	67-68-5	200-664-3	Warning. 2 H315 Causes skin irritation.  Warning. 3 H226 Flammable liquid and vapour.	≤ 10
Acetone	67-64-1	200-662-2	Danger. 2 H225 Highly Flammable liquid and vapour.  Warning. 2 H319 Causes serious eye irritation. STOT 3	≤ 10



Rev. Date: Aug 17, 2021

**Revision: 4** 

Page 3 of 7

P.O. Box 3286 - Logan, Utah 84323, U.S.A. - Tel. (800) 729-8350 - Tel. (435) 755-9848 - Fax (435) 755-0015 - www.scytek.com

			H336 May cause drowsiness or dizziness.	
3-3'-5-5'- Tetramethylbenzidine	64285-73-0	264-769-6	Warning. 2 H315 Causes skin irritation. 2 H319 Causes serious eye irritation. 3 H335 May cause respiratory irritation.	≤ 0.1
Diocyl sulfosuccinate sodium salt	577-11-7	209-406-4	Danger. 1.H318 Causes severe eye damage. 2 H315 causes skin irritation. 3 H402 Harmful to aquatic life.	≤ 1
Hydrogen Peroxide	7722-84-1	231-765-0	Danger. 1. H271 May cause fire or explosion; strong oxidizer.  Danger. 1B.H314 Causes severe skin burns and eye damage.  Warning. 4 H302 Harmful if swallowed. H333 May be harmful if inhaled.  Warning. H402 Harmful to aquatic life.	≤ 0.1

#### **Section 4. First Aid Measures**

#### 4.1 Description of first aid measures

Eye Contact: Check for and remove contact lenses. Immediately flush eyes with copious amounts of water and get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and wash contact area with mild soap and copious amounts of water. Get medical attention if irritation develops.

**Inhalation:** If inhaled, remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms worsen.

**Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as collar, tie, belt or waistband. Get immediate medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

See section 2.2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

#### **Section 5. Fire Fighting Measures**

5.1 Extinguishing Media	Extinguish fire using water spray, carbon dioxide, chemical foam, or dry chemical.
5.2 Special hazards arising from the substance or mixture	May produce flammable vapors when heated during fire conditions.



Revision: 4

11/13-51/

Page 4 of 7

P.O. Box 3286 - Logan, Utah 84323, U.S.A. - Tel. (800) 729-8350 - Tel. (435) 755-9848 - Fax (435) 755-0015 - www.scytek.com

5.3 Advice for	As with any fire, wear personal protection equipment, including a self-contained breathing apparatus
firefighters	(S.C.B.A.)

Rev. Date: Aug 17, 2021

#### Section 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Wear chemical resistant clothing, gloves, and eye protection. Wear NIOSH/MSHA approved breathing apparatus.

#### 6.2 Environmental precautions

Keep material away from heat, flame, ignition sources, and reactive materials. Don't allow product to enter drain.

#### 6.3 Methods and materials for containment and cleaning up

Wipe up or absorb spill using inert absorbent and place in a suitable waste container for disposal.

### Section 7. Handling and Storage

#### 7.1 Precautions for safe handling.

Avoid contact with skin and eyes.

Wash thoroughly after handling.

Avoid breathing vapor.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store in well ventilated area.

Keep container tightly closed.

Store at 2-8°C.

#### 7.3 Specific end use(s).

See section 1.2

#### Section 8. Exposure Controls / Personal Protection

8.1 Control parameters	Exposure Limits:
•	Methanol:
	NIOSH REL: TWA 200 ppm (260 mg/m³) ST 250 ppm (325 mg/m³) [skin]
	<b>OSHA PEL</b> : TWA 200 ppm (260 mg/m³)
	ACGIH TLV: TWA 200 ppm (262 mg/m³)
	STEL 250 ppm (328 mg/m³)
	Acetone:
	<b>OSHA PEL</b> : 1,000 ppm (2,400 mg/m³) TWA
	NIOSH REL: 250 ppm (590 mg/m³) TWA
	ACGIH: 500 ppm (1,188 mg/m³) TWA
	750 ppm (1,782 mg/m³) STEL
8.2 Exposure controls	Personal Protective Equipment (PPE):
_	Eye/Face protection.
	Safety glasses or goggles are required.
	Skin protection.
	Protective clothing is required.
	Hand protection.
	Chemical resistant gloves are required.
	Glove material must be resistant to the components of this product.
	Consult glove manufacturer for specific recommendations of appropriate material and thickness of glove.
	Respiratory protection.
	Avoid breathing vapor.
	Environmental exposure controls.
	Avoid releasing large quantities into the environment.
	No additional information.
Engineering Controls	Working area should be adequately large and well ventilated to prevent concentration of vapors.



Rev. Date: Aug 17, 2021

**Revision: 4** 

Page 5 of 7

P.O. Box 3286 - Logan, Utah 84323, U.S.A. - Tel. (800) 729-8350 - Tel. (435) 755-9848 - Fax (435) 755-0015 - www.scytek.com

Provide mechanical exhaust ventilation or other engineering controls to keep airborne concentrations of vapors below their respective threshold limits.

## Section 9. Physical and Chemical Properties

Physical State	Liquid
Color	Translucent, clear to slightly yellow.
Odor	Mild alcohol odor.
Odor Threshold	Unknown
pH	Unknown
Melting Point/ Freezing Point	Unknown
Initial Boiling Point	Unknown
Flash Point	Unknown
Evaporation Rate	Unknown
Flammability (solid, gas)	Unknown
Upper/Lower Flammability Limits	Unknown
Vapor Pressure	Unknown
Vapor Density	Unknown
Relative Density	Unknown
Solubility(ies)	Water
Partition Coefficient:	Unknown
n-octanol/water	
Auto-Ignition Temperature	Unknown
Decomposition Temperature	Unknown
Viscosity	Unknown
Explosive Properties	Not explosive.
Oxidizing Properties	Unknown

# Section 10. Stability and Reactivity

10.1 Reactivity	No relevant data available.
10.2 Chemical Stability	Stable under normal temperatures and pressures.
10.3 Possibility of Hazardous Reactions	No hazardous reactions known.
10.4 Conditions to Avoid	Fire, static electricity, direct sunlight.
10.5 Incompatible Materials	Strong oxidizing agents such as sulfuric acid, nitrates, and perchlorates.
10.6 Hazardous Decomposition Materials	May release carbon dioxide, carbon monoxide, nitrogen oxides, and formaldehyde under fire conditions.

### Section 11. Toxicological Information

11.1 Information on	Acute Toxicity.
Toxicological Effects.	Methanol:
	Oral LD50
	LDLO Oral - Human - 143 mg/kg
	and diarrhea.
	LD50 Oral - rat - 1,187 - 2,769 mg/kg



Rev. Date: Aug 17, 2021

**Revision: 4** 

Page 6 of 7

P.O. Box 3286 - Logan, Utah 84323, U.S.A. - Tel. (800) 729-8350 - Tel. (435) 755-9848 - Fax (435) 755-0015 - www.scytek.com

Inhalation LC50 LC50 Inhalation - rat - 4 h - 128.2 mg/l LC50 Inhalation - rat - 6 h - 87.6 mg/l Dermal LD50 LD50 Dermal - rabbit - 17,100 mg/kg Dimethylsulfoxide: LD50 Oral - rat - 14,500 mg/kg LC50 Inhalation - rat - 4 h - 40250 ppm LD50 Dermal - rabbit - > 5,000 mg/kg Skin Corrosion/Irritation. May be irritating to skin and mucous membranes.
LC50 Inhalation - rat - 6 h - 87.6 mg/l  Dermal LD50  LD50 Dermal - rabbit - 17,100 mg/kg  Dimethylsulfoxide:  LD50 Oral - rat - 14,500 mg/kg  LC50 Inhalation - rat - 4 h - 40250 ppm  LD50 Dermal - rabbit - > 5,000 mg/kg  Skin Corrosion/Irritation.  May be irritating to skin and mucous membranes.
Dermal LD50 LD50 Dermal - rabbit - 17,100 mg/kg  Dimethylsulfoxide: LD50 Oral - rat - 14,500 mg/kg LC50 Inhalation - rat - 4 h - 40250 ppm LD50 Dermal - rabbit - > 5,000 mg/kg Skin Corrosion/Irritation. May be irritating to skin and mucous membranes.
LD50 Dermal - rabbit - 17,100 mg/kg  Dimethylsulfoxide:  LD50 Oral - rat - 14,500 mg/kg  LC50 Inhalation - rat - 4 h - 40250 ppm  LD50 Dermal - rabbit - > 5,000 mg/kg  Skin Corrosion/Irritation.  May be irritating to skin and mucous membranes.
Dimethylsulfoxide:  LD50 Oral - rat - 14,500 mg/kg  LC50 Inhalation - rat - 4 h - 40250 ppm  LD50 Dermal - rabbit - > 5,000 mg/kg  Skin Corrosion/Irritation.  May be irritating to skin and mucous membranes.
LD50 Oral - rat - 14,500 mg/kg  LC50 Inhalation - rat - 4 h - 40250 ppm  LD50 Dermal - rabbit - > 5,000 mg/kg  Skin Corrosion/Irritation.  May be irritating to skin and mucous membranes.
LC50 Inhalation - rat - 4 h - 40250 ppm  LD50 Dermal - rabbit - > 5,000 mg/kg  Skin Corrosion/Irritation.  May be irritating to skin and mucous membranes.
LD50 Dermal - rabbit - > 5,000 mg/kg <b>Skin Corrosion/Irritation.</b> May be irritating to skin and mucous membranes.
Skin Corrosion/Irritation.  May be irritating to skin and mucous membranes.
May be irritating to skin and mucous membranes.
Serious Eye Damage/Irritation.
May be irritating to eye.
Respiratory or skin sensitization.
No relevant data available.
Germ Cell Mutagenicity.
No relevant data available.
Carcinogenicity. International Agency for Research on Cancer (IARC).
None of the components are listed.
National Toxicology Program (NTP).
None of the components are listed.

## Section 12. Ecological Information

12.1 Toxicity	Fish: No relevant studies identified.  Crustacea: No relevant studies identified.
	Algae/Aquatic Plants: No relevant studies identified.
	Other Organisms: No relevant studies identified.
12.2 Persistence and Degradability.	No relevant studies identified.
12.3 Bioaccumulative Potential.	No relevant studies identified.
12.4 Mobility in Soil.	Miscible in water. May spread in water systems. This component is non-volatile.
Additional Remarks	None.
12.5 Results of PBT and vPvB Assessment.	PBT: This mixture does not contain any substances that are assessed to be a PBT.  vPvB: This mixture does not contain any substances that are assessed to be a vPvB.

# Section 13. Disposal Considerations

13.1 Waste Disposal Methods.	Sewage disposal is discouraged. Waste should not be disposed of by release to sewers. Dispose waste in accordance with federal, state and local environmental control regulations.
Product/Packaging Disposal.	Final decisions on the appropriate waste management method must be in line with local, regional and national regulations.
Other Disposal Recommendations.	No relevant data available.

### **Section 14. Transport Information**

14.1 UN Number	1230
14.2 UN Proper Shipping Name	Methanol



Rev. Date: Aug 17, 2021

**Revision: 4** 

Page 7 of 7

P.O. Box 3286 - Logan, Utah 84323, U.S.A. - Tel. (800) 729-8350 - Tel. (435) 755-9848 - Fax (435) 755-0015 - www.scytek.com

14.3 Transport Hazard Class(es)	3 1230
14.4 Packing Group	
14.5 Environmental Hazards	Marine Pollutant: No
14.6 Special Precautions for User	Not applicable.

## Section 15. Regulatory Information

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture.		
Extremely Hazardous Substances; Section 355	None of the components in this mixture are listed.	
Toxic Substances Control Act; TSCA	All of the components in this mixture are listed.	
California Proposition 65	Methanol is listed as a having developmental toxicity.	
Right To Know Components	Methanol CAS# 67-56-1:  Massachusetts, Pennsylvania, New Jersey, California, Minnesota 3-3'-5-5'-Tetramethylbenzidine CAS# 64285-73-0:  Pennsylvania, New Jersey Acetone CAS# 67-64-1:  Massachusetts, Pennsylvania, New Jersey, California, Minnesota	

## Section 16. Other Information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. ScyTek Laboratories shall not be held liable for any damage resulting from handling or from contact with the above product.